

# Wascomat Soft-Mount Washers for OPL

## NOW WITH 400-450 G-FORCE EXTRACTION.

Built to last, Wascomat's EX washers are designed for efficiency and superior wash results. The high G-force extraction cuts drying time resulting in lower utility costs and higher laundry room productivity. Plus Wascomat EX washers are easy to install anywhere: on wood floors, upper levels, and over basements.



### Features and benefits:

- Up to 450G ultra high-speed extraction for super fast drying & low energy costs
- Heavy-duty construction for demanding applications
- Efficient frequency-controlled motor reduces peak power demand for energy savings
- Optional steam injection or electric heating for precise control of water temperature
- Built-in connection for automatic liquid injector
  - Compass Pro provides 5 liquid chemical signals
  - Clarus Control® provides 4 liquid chemical signals, expandable to 8 signals
- Standard 4-compartment supply dispenser for liquid or powder supplies
- Built-in diagnostics and statistics

### Compass Pro features:

- Customize wash programs to raise efficiencies and lower costs
- 18 languages available
- Reduce operator error by displaying only the programs you use
- Up to 55 programs available, ability to create 15 custom programs
- USB on front for easy programming
- Real-time clock for automatic start

### Clarus Control® features:

- Fully programmable – store up to 192 custom programs
- All wash parameters can be programmed and customized
- Programming from keypad or download via memory card

### Environmentally responsible.

With more than a century of experience behind every machine, Wascomat's state-of-the-art products are engineered for quality, energy savings, and water efficiency. When you buy Wascomat, you are truly investing in the future of your business.

## Available with two types of program controls.

- Compass Pro Microprocessor
- Clarus Control®

## Best in the industry!

**External Liquid Chemical Manifold** for improved reliability, maintenance and flushing using built in water reservoir to promote 24/7 diluted chemicals in dispensing system – prevents chemical damage to machine. Best in the industry!

*Shock absorbing suspension system allows for easy installation on wood floors, upper floors, and over basements. Available in 45 (Energy Star certified), 60, and 75 lb. capacities.*



[www.laundrylux.com](http://www.laundrylux.com)

Model	EX745		EX760		EX775	
Capacity (lbs/kg)	45	20	60	27	75	33
Width (in/mm) *with optional soap injector	38 3/16	970	40 3/16	1020	40 3/16	1020
Depth Overall (in/mm) *with optional soap injector	37 1/5	945	37 5/8	955	44 11/16	1135
Tilting Depth Overall (in/mm)	n/a		n/a		n/a	
Height (in/mm)	55 1/2	1410	56 7/8	1445	56 7/8	1445
Door Opening Diameter (in/mm)	17 1/8	435	17 1/8	435	17 1/8	435
Height to Bottom of Door (in/mm)	18 1/2	470	19 11/16	500	19 11/16	500
Cylinder Volumm (ft3/l)	6.4	180	8.5	240	10.6	300
Cylinder diameter (in/mm)	28 9/16	725	19 11/16	500	19 11/16	500
Net weigh (lb/kg)	783	356	880	400	1120	509
Crated Weight (lbs/kg)	827	376	986	448	1162	528
<b>Operating Speeds</b>						
Extract (rpm/G-factor)	930/350		890/350		820/300	
Wash (rpm)	44		42		42	
<b>Electrical Requirements (standard)</b>						
Voltage/Frequency/Phase	208-240/60/1		208-240/60/1		208-240/60/1	
Full Load Current (Amps) /Ckt Breaker (Amps)	11/15		12.5/20		10.1/15	
<b>Water Information</b>						
Inlet Fittings (1 hot, 1 cold, 1 hot or cold)	3/4	DN20	3/4	DN20	4-Mar	DN20
Flow (gpm/lpm) @ 45 psi (per inlet)	5	20	16	60	16	60
Recommended Water Pressure (psi/kPa)	30 - 60	150 - 400	30 - 60	150 - 400	30 - 60	150 - 400
Steam Supply (w/ heating option) (psi/kPa)	40 - 70	300 - 500	40 - 70	300 - 500	40 - 70	300 - 500
Steam Inlet*	1/2	DN15	1/2	DN15	1/2	DN15

Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, common-trip, circuit breakers ONLY. Warranty void if not properly installed. Solid-mount machines require a concrete foundation, and are not suitable for upper-floor or above-basement installations. Contact Laundrylux for more information and for availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.

**Call today for information on the full line of Wascomat Commercial Laundry Equipment and low-cost financing and leasing.**



**Laundrylux • 461 Doughty Blvd., Inwood, NY 11096-0338**  
**Sales & Administration:** Tel: 516-371-4400 • Fax: 516-371-4204 • e-mail: sales@laundrylux.com  
**Parts:** Tel: 516-371-2000 • Fax: 516-371-4029 • e-mail: parts@laundrylux.com  
**Technical Support:** Tel: 516-371-0700 • Fax: 516-371-4029 • e-mail: service@laundrylux.com  
**En Mexico:** Llame gratis a este numero 001-800-010-1010

